

Aluminum Oxide Resin Cloth Open

Features

- Light brown aluminum oxide abrasive
- Full resin bond system
- X-weight cotton backing
- Open coat

Benefits

- Uniform scratch pattern
- Increased strength
- Resists loading

Applications include finishing of wood and non-ferrous metals.



PART NO.	GRADING		BELTS/PKG.	BELTS/CASE
25" x 75"				
05539599963	80	XC 0776 O	3	3
05539599962	100	XC 0776 O	5	5
05539599961	120	XC 0776 O	5	5
05539599960	150	XC 0776 O	5	5
37" x 60"				
05539599978	60	XC 0776 O	3	3
05539599977	80	XC 0776 O	3	3
05539599976	100	XC 0776 O	5	5
05539599975	120	XC 0776 O	5	5
05539599974	150	XC 0776 O	5	5
05539599973	180	XC 0776 O	5	5

PART NO.	GRADING		BELTS/PKG.	BELTS/CASE
37" x 75"				
05539599992	60	XC 0776 O	3	3
05539599991	80	XC 0776 O	3	3
05539599990	100	XC 0776 O	5	5
05539599989	120	XC 0776 O	5	5
05539599988	150	XC 0776 O	5	5
05539599987	180	XC 0776 O	5	5



Troubleshooting Guide

PROBLEM	SUGGESTED CORRECTION - CONTACT WHEELS									
	HARDER WHEEL	SOFTER WHEEL	LARGER GROOVE/LAND	SMALLER GROOVE/LAND	DRESS WHEEL	HIGHER SPEED	LOWER SPEED	STANDARD SERRATION	LARGER WHEEL	SMALLER WHEEL
DULLING	•		•				•			•
LOADING			•							•
OVER-AGGRESSIVENESS		•		•				•	•	
SLOW CUTTING	•		•			•				•
SCRATCHES TOO DEEP		•		•				•	•	
BURNING	•						•			
NON-CONFORMITY		•	•				•		•	
DUBBING EDGES	•									
SHEDDING (ABRASIVES)		•		•	•	•		•	•	
CHATTER		•			•			•	•	

COATED

11



For additional sizes and specifications of belts, refer to FastTrack Belt Service on pages 2 - 5.