

Model Number	Nominal Size (Inches) W x H x D	Actual Size (Inches) W x H x D	Rated Air Flow (CFM)	Initial Resistance (IN W.G.)			Media Area (Square Feet)
				90-95%	80-85%	60-65%	
CS-*04-C1	24 x 24 x 4	23-3/8 x 23-3/8 x 3-3/4	2000	.65	.55	.40	94
CS-*12-C1	20 x 25 x 4	19-3/8 x 24-3/8 x 3-3/4	1750	.65	.55	.40	84
CS-*15-C1	20 x 24 x 4	19-3/8 x 23-3/8 x 3-3/4	1650	.65	.55	.40	82
CS-*13-C1	20 x 20 x 4	19-3/8 x 19-3/8 x 3-3/4	1400	.65	.55	.40	65
CS-*11-C1	18 x 24 x 4	17-3/8 x 23-3/8 x 3-3/4	1500	.65	.55	.40	70
CS-*10-C1	16 x 25 x 4	15-3/8 x 24-3/8 x 3-3/4	1400	.65	.55	.40	65
CS-*09-C1	16 x 20 x 4	15-3/8 x 19-3/8 x 3-3/4	1100	.65	.55	.40	52
CS-*03-C1	12 x 24 x 4	11-3/8 x 23-3/8 x 3-3/4	1000	.65	.55	.40	46
CS-*02-C1	24 x 24 x 2	23-3/8 x 23-3/8 x 1-3/4	1000	.46	.43	.28	42
CS-*08-C1	20 x 25 x 2	19-3/8 x 24-3/8 x 1-3/4	875	.46	.43	.28	37
CS-*16-C1	20 x 24 x 2	19-3/8 x 23-3/8 x 1-3/4	825	.46	.43	.28	35
CS-*14-C1	20 x 20 x 2	19-3/8 x 19-3/8 x 1-3/4	700	.46	.43	.28	29
CS-*07-C1	18 x 24 x 2	17-3/8 x 23-3/8 x 1-3/4	750	.46	.43	.28	32
CS-*06-C1	16 x 25 x 2	15-3/8 x 24-3/8 x 1-3/4	700	.46	.43	.28	29
CS-*05-C1	16 x 20 x 2	15-3/8 x 19-3/8 x 1-3/4	550	.46	.43	.28	24
CS-*01-C1	12 x 24 x 2	11-3/8 x 23-3/8 x 1-3/4	500	.46	.43	.28	21



* - Filter Efficiency (9 = 90-95%, 8 = 80-85%, 6 = 60-65%)

STANDARD CONSTRUCTION

1. High Efficiency, Microglass Paper Media
2. Corrugated Aluminum Separators With Rolled Edges
3. 24 Gauge Galvanized Steel Cell Sides
4. Expanded Metal Grid on Both Sides

NOTES

1. Final Resistance: 1.5" W.G.
2. Rated Velocity 4" Deep - 500 FPM
3. Rated Velocity 2" Deep - 250 FPM
4. Class 1 Filter Per U.L. Standard 900
5. Maximum Operating Temperature: 750 deg. F
Do Not Exceed 1.2" W.G. Above 250 deg. F
6. Optional High Temperature Gasket Available
U - Upstream Gasket (Ex: CS-904-U)
D - Downstream Gasket
UD - Both Sides
7. Reverse Pleat Orientation Available
Add "-R" to Model Number (Ex: VMA-904-R)
8. Special Sizes Available

 ONE SOURCE FOR AIR FILTRATION PRODUCTS P.O. Box 32578 Louisville, KY 40232 P: 502-969-2304 F: 502-961-0930	TOLERANCES UNLESS OTHERWISE SPECIFIED		DRAWING NAME VARIFLOW COMPACT SERIES	
	FRACTIONAL DECIMAL ANGLES	APPROVED BY 	SPECIFICATION NO. MKT-B-00149	PAGE 1 OF 1
CONTACT FACTORY TO VERIFY REVISION LEVEL	ALL DIMENSIONS IN INCHES	SCALE NONE	DVG. SIZE A	REVISION NEW
CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY AIRGUARD. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.				