

POWDER-FREE LATEX **EXTENDED CUFF EXAMINATION GLOVES**

Recommended for use in the following industries: EMS, Lab, and Industrial Safety

Textured for a secure grip. Synetron® is polymer-coated for easy donning. This glove meets the single-use emergency medical examination glove requirements of NFPA 1999, Standard on Protective Clothing for Emergency Medical Operations, 2008 edition.*

*Certification on file.

FEATURES AND BENEFITS:

- Interior/exterior polymer system provides superior anti-sticking properties resulting in highly effective donning in wet, damp or dry conditions
- Extended cuff for increased protection over the wrist and forearm
- Fine fingertip sensitivity for finding a pulse and starting an I.V.

Synetron's Attributes		ASTM D 3578	Synetron®
	Length (mm/in):	220 / 8.7	290 / 11.4
	Cuff Thickness (mils):	n/a	6.7
	Palm Thickness (mils):	min. 3.1	9.1
	Finger Thickness (mils):	min. 3.1	11.8
	Tensile Strength		
EXTRA-LARGE	Before Aging (MPa):	min. 18	21
50 ambidextrous gloves per dispenser box, by weight	After Aging (MPa):	min. 14	18
CONTROL C	Elasticity/Elongation:		
	Before Aging (%):	min. 650	750
	After Aging (%):	min. 500	600
	Reduced Protein Rating:	max. 200 µg/dm2	max. 50 µg/g
Order #	Material: Latex Usage: For single use only		
SSY-911-S XLSY-911-XL	Type: Non-sterile		
MSY-911-M 2XLSY-911-XXL	Color: Natural	Size: S - 3XL	
LSY-911-L 3XLSY-911-3XL	Cuff: Extended, beaded	Glove Exterior:	Fully textured
E	Glove Interior: Powder-free		T dify toxtaroa
Caution: This product contains natural rubber latex (latex) which may cause allergic	Pkg. S-2XL: 500 gloves per case, by weight		
reactions. Safe use of this glove by or on latex sensitized individuals has not been established.	10 boxes per ca		
	Pkg. 3XL: 400 gloves per case, by weight 10 boxes per case		
To boxes per case			

See for yourself why Microflex® gloves are the first choice of exam glove users nationwide. Contact a Microflex® distributor today to purchase quality Microflex® products. For the name of a distributor in your area, call: (800) 876-6866. Fax: (800) 876-6632.

R